



RINGSTEEKSLEUTEL 400, LICHT GEBOGEN



Kenmerken

- DIN 3113 A
- ISO 3318
- ISO 7738

Varianten (39)

| Artikelnummer | Artikelnummer fabrikant | Sleutelwijdte (mm) | Lengte (mm) | Gewicht (gr) | Uitvoering |
|---------------|-------------------------|--------------------|-------------|--------------|------------|
| 41-10209-274 | 400-5,5MM (00400005582) | 5.5 | 100 | 14 | |
| 41-10209-277 | 400-6MM (00400006082) | 6.0 | 100 | 14 | |
| 41-10209-280 | 400-7MM (00400007082) | 7.0 | 110 | 16 | |
| 41-10209-285 | 400-8MM (00400008082) | 8.0 | 120 | 23 | |
| 41-10209-288 | 400-9MM (00400009082) | 9.0 | 130 | 33 | |
| 41-10209-220 | 400-10MM (00400010082) | 10.0 | 140 | 40 | |
| 41-10209-222 | 400-11MM (00400011082) | 11.0 | 150 | 48 | |
| 41-10209-225 | 400-12MM (00400012082) | 12.0 | 160 | 58 | |
| 41-10209-227 | 400-13MM (00400013082) | 13.0 | 170 | 63 | |
| 41-10209-230 | 400-14MM (00400014082) | 14.0 | 180 | 88 | |
| 41-10209-232 | 400-15MM (00400015082) | 15.0 | 190 | 97 | |
| 41-10209-235 | 400-16MM (00400016082) | 16.0 | 200 | 105 | |
| 41-10209-237 | 400-17MM (00400017082) | 17.0 | 210 | 135 | |
| 41-10209-239 | 400-18MM (00400018082) | 18.0 | 220 | 145 | |
| 41-10209-241 | 400-19MM (00400019082) | 19.0 | 230 | 155 | |
| 41-10209-251 | 400-20MM (00400020082) | 20.0 | 240 | 175 | |
| 41-10209-252 | 400-21MM (00400021082) | 21.0 | 250 | 200 | |
| 41-10209-253 | 400-22MM (00400022082) | 22.0 | 260 | 230 | |

| Artikelnummer | Artikelnummer fabrikant | Sleutelwijdte (mm) | Lengte (mm) | Gewicht (gr) | Uitvoering |
|---------------|-------------------------|--------------------|-------------|--------------|--------------|
| 41-10209-254 | 400-23MM (00400023082) | 23.0 | 270 | 255 | |
| 41-10209-255 | 400-24MM (00400024082) | 24.0 | 280 | 280 | |
| 41-10209-256 | 400-25MM (00400025082) | 25.0 | 290 | 300 | |
| 41-10209-258 | 400-26MM (00400026082) | 26.0 | 300 | 335 | |
| 41-10209-259 | 400-27MM (00400027082) | 27.0 | 310 | 375 | |
| 41-10209-260 | 400-28MM (00400028082) | 28.0 | 320 | 400 | |
| 41-10209-261 | 400-29MM (00400029082) | 29.0 | 330 | 440 | |
| 41-10209-265 | 400-30MM (00400030082) | 30.0 | 340 | 490 | |
| 41-10209-266 | 400-32MM (00400032082) | 32.0 | 360 | 590 | |
| 41-10209-267 | 400-34MM (00400034082) | 34.0 | 380 | 680 | |
| 41-10209-268 | 400-36MM (00400036082) | 36.0 | 400 | 1090 | |
| 41-10209-269 | 400-38MM (00400038082) | 38.0 | 400 | 1070 | |
| 41-10209-270 | 400-41MM (00400041082) | 41.0 | 450 | 1450 | |
| 41-10209-271 | 400-46MM (00400046082) | 46.0 | 500 | 1960 | |
| 41-10209-275 | 400-50MM (00400050082) | 50.0 | 540 | 2600 | |
| 41-10209-276 | 400-55MM (00400055080) | 55.0 | 610 | 2850 | Diep gebogen |
| 41-10209-278 | 400-60MM (00400060080) | 60.0 | 660 | 3600 | Diep gebogen |
| 41-10209-279 | 400-65MM (00400065080) | 65.0 | 710 | 4550 | Diep gebogen |
| 41-10209-283 | 400-70MM (00400070080) | 70.0 | 760 | 5800 | Diep gebogen |
| 41-10209-284 | 400-75MM (00400075080) | 75.0 | 810 | 6650 | Diep gebogen |
| 41-10209-286 | 400-80MM (00400080080) | 80.0 | 860 | 8500 | Diep gebogen |