



RINGSTEEKSLEUTEL 50810, LICHT GEBOGEN



Kenmerken

- DIN 3113A
- ISO 7738
- Chroom-Vanadium, verchromd
- Profiel beschermer

Varianten (21)

| Artikelnummer | Artikelnummer fabrikant | Sleutelwijdte mm | Lengte (mm) | Gewicht (gr) |
|---------------|-------------------------|------------------|-------------|--------------|
| 41-10209-529 | 50810-6 (50810006080) | 6.0 | 100 | 12 |
| 41-10209-530 | 50810-7 (50810007080) | 7.0 | 110 | 18 |
| 41-10209-531 | 50810-8 (50810008080) | 8.0 | 120 | 23 |
| 41-10209-532 | 50810-9 (50810009080) | 9.0 | 130 | 33 |
| 41-10209-512 | 50810-10 (50810010080) | 10.0 | 140 | 40 |
| 41-10209-513 | 50810-11 (50810011080) | 11.0 | 150 | 48 |
| 41-10209-514 | 50810-12 (50810012080) | 12.0 | 160 | 58 |
| 41-10209-515 | 50810-13 (50810013080) | 13.0 | 170 | 63 |
| 41-10209-516 | 50810-14 (50810014080) | 14.0 | 180 | 88 |
| 41-10209-517 | 50810-15 (50810015080) | 15.0 | 190 | 97 |
| 41-10209-518 | 50810-16 (50810016080) | 16.0 | 200 | 105 |
| 41-10209-519 | 50810-17 (50810017080) | 17.0 | 210 | 130 |
| 41-10209-520 | 50810-18 (50810018080) | 18.0 | 220 | 145 |
| 41-10209-521 | 50810-19 (50810019080) | 19.0 | 230 | 145 |
| 41-10209-522 | 50810-20 (50810020080) | 20.0 | 240 | 165 |
| 41-10209-523 | 50810-21 (50810021080) | 21.0 | 250 | 190 |
| 41-10209-524 | 50810-22 (50810022080) | 22.0 | 260 | 225 |
| 41-10209-525 | 50810-24 (50810024080) | 24.0 | 280 | 265 |

| Artikelnummer | Artikelnummer fabrikant | Sleutelwijdte mm | Lengte (mm) | Gewicht (gr) |
|---------------|-------------------------|------------------|-------------|--------------|
| 41-10209-526 | 50810-27 (50810027080) | 27.0 | 310 | 330 |
| 41-10209-527 | 50810-30 (50810030080) | 30.0 | 340 | 430 |
| 41-10209-528 | 50810-32 (50810032080) | 32.0 | 360 | 515 |