



## RINGSTEEKSLEUTEL 50810, LICHT GEBOGEN



### Kenmerken

- DIN 3113A
- ISO 7738
- Chroom-Vanadium, verchromd
- Profiel beschermer

### Varianten (21)

Artikelnummer	Artikelnummer fabrikant	Sleutelwijdte mm	Lengte (mm)	Gewicht (gr)
41-10209-529	50810-6 (50810006080)	6.0	100	12
41-10209-530	50810-7 (50810007080)	7.0	110	18
41-10209-531	50810-8 (50810008080)	8.0	120	23
41-10209-532	50810-9 (50810009080)	9.0	130	33
41-10209-512	50810-10 (50810010080)	10.0	140	40
41-10209-513	50810-11 (50810011080)	11.0	150	48
41-10209-514	50810-12 (50810012080)	12.0	160	58
41-10209-515	50810-13 (50810013080)	13.0	170	63
41-10209-516	50810-14 (50810014080)	14.0	180	88
41-10209-517	50810-15 (50810015080)	15.0	190	97
41-10209-518	50810-16 (50810016080)	16.0	200	105
41-10209-519	50810-17 (50810017080)	17.0	210	130
41-10209-520	50810-18 (50810018080)	18.0	220	145
41-10209-521	50810-19 (50810019080)	19.0	230	145
41-10209-522	50810-20 (50810020080)	20.0	240	165
41-10209-523	50810-21 (50810021080)	21.0	250	190
41-10209-524	50810-22 (50810022080)	22.0	260	225
41-10209-525	50810-24 (50810024080)	24.0	280	265

Artikelnummer	Artikelnummer fabrikant	Sleutelwijdte mm	Lengte (mm)	Gewicht (gr)
41-10209-526	50810-27 (50810027080)	27.0	310	330
41-10209-527	50810-30 (50810030080)	30.0	340	430
41-10209-528	50810-32 (50810032080)	32.0	360	515